



| | MX 20 | MX 30 |
|--------------------------------|------------------------|------------------------|
| Control system | E | E |
| Cooling system | A | A |
| Production in 24 h | 20 kg Up to 1111 cubes | 30 kg Up to 1666 cubes |
| Production per cycle | 24 ice cubes | 28 ice cubes |
| Storage capacity | 6 kg Approx 333 cubes | 10 kg Approx 555 cubes |
| Voltage Standard | 230 V ~ 50 Hz | 230 V ~ 50 Hz |
| Power consumption | 350 W | 450 W |
| Type of refrigerant | R 404 A | R 404 A |
| Dimensions (W x D x H) | 365x495x600 mm | 365x495x690 mm |
| Feet | 110-140mm | 110-140mm |
| Net Weight | 33 kg | 36 kg |
| Packing dimensions (W x D x H) | 445x575x700 mm | 445x575x790 mm |
| Gross weight | 37 kg | 40 kg |

E = Electronic control

A = Air cooled

| | | | | | | |
|-------------------|------|------|------|------|------|-----|
| WATER-TEMPERATURE | 38°C | 70% | 65% | 60% | 55% | 50% |
| | 32°C | 80% | 70% | 60% | 55% | 55% |
| | 25°C | 90% | 80% | 70% | 60% | 60% |
| | 15°C | 100% | 100% | 80% | 70% | 65% |
| | 10°C | 105% | 100% | 90% | 80% | 70% |
| | 10°C | 21°C | 32°C | 38°C | 43°C | |

AMBIENT-TEMPERATURE

